


Interior Finish: SC - Sorensen Center

Paint

PNT-01
Type: Field
MFG: PPG
Color: 9730020C0012189
Name: Oyster White



PNT-02
Type: Accent
MFG: Sherwin Williams
Color: SW 7674
Name: Peppercorn



PNT-03
Type: Accent
MFG: Sherwin Williams
Color: SW 6258
Name: Tricorn Black



Paint

PNT-04
Type: Accent
MFG: Benjamin Moore
Color: 2037-20
Name: Jade Green



PNT-05
Type: Accent
MFG: Sherwin Williams
Color: SW 6734
Name: Espalier



PNT-06
Type: Accent
MFG: Sherwin Williams
Color: SW 7007
Name: Ceiling Bright White




Flooring - Carpet


CPT-01
MFG: Interface
Style: WW880 #128200AK00
Color: 105360 Flannel Loomt
Size: 25 cm x 1 m



CPT-02
MFG: Interface
Style: On Line #138700AK00
Color: 103796 Forest
Size: 25 cm x 1 m




CPT-03
MFG: Interface
Style: WW870 #138930AK00
Color: 105344 Flannel Weft
Size: 25 cm x 1 m




Interior Finish: SC - Sorensen Center

Flooring - Carpet

CPT-04
MFG: Interface
Style: WW890 #128240AK00
Color: 105384 Flannel Dobby
Size: 25 cm x 1 m



CPT-05
MFG: Interface
Style: Entropy
Color: 7200 Variations
Size: 50 cm x 50 cm



CPT-06
MFG: Interface
Style: WW880
Color: 105361 Charcoal Loom
Size: 25 cm x 1 m




CPT-07
MFG: Interface
Style: WW870
Color: 105345 Charcoal Weft
Size: 25 cm x 1 m



Flooring - Carpet

CPT-08
MFG: Interface
Style: WW890
Color: 105385 Charcoal
Dobby
Size: 25 cm x 1 m



EM-01
MFG: Interface
Style: SR999
Color: 104945 Onyx
Size: 50 cm x 50 cm



Flooring - Tile

PS-01
MFG: Levantina
Style: Techlam
Color: Basic Black
Size: 300 x 100 cm x 5+mm



TL-01
MFG: Crossville
Style: RET12.10424PTN
Color: Racing Green
Size: 4" x 24"



TL-02
MFG: Crossville
Style: RET12.10624PTN
Color: Racing Green
Size: 6 X 24"




TL-03
MFG: Crossville
Style: RET05.10424PTN
Color: Snow Blind
Size: 4" x 24"




Flooring - Tile


TL-04
MFG: Crossville
Style: RET05.10624PTN
Color: Snow Blind
Size: 6" x 24"




TL-05
MFG: Crossville
Style: RET08.10424PTN
Color: Mercurial Pattern
Size: 4" x 24"



TL-06
MFG: Crossville
Style: RET08.10624PTN
Color: Mercurial Pattern
Size: 6" x 24"



TL-07
MFG: Crossville
Style: RET07.10424PTN
Color: Leaden Pattern
Size: 4" x 24"



Interior Finish: SC - Sorensen Center

Flooring - Tile


TL-08
MFG: Crossville
Style: RET07.10624PTN
Color: Leaden Pattern
Size: 6" x 24"



TL-13
MFG: Daltile
Style: Color Wheel Linear
Color: Emerald 115
Size: 4" x 16"



TL-14
MFG: Crossville
Style: Retro Active 2.0
RET07.11224UPS
Color: Leaden
Size: 12" x 24"




TL-16
MFG: Contempo
Style: Flow Diamond
Color: White
Size: 5.5" x 9.5"




Flooring - Tile

TL-17
MFG: Contempo
Style: Flow Diamond
Color: Taupe
Size: 5.5" x 9.5"



TL-18
MFG: Daltile
Style: Rima Hex
Color: Black
Size: 7" x 8"




Flooring

RF-01
Type: Luxury Vinyl Tile
MFG: Shaw Contract
Style: Inlet 0926V
Color: Spindle 26140
Size: 9' x 48'



RF-02
Type: Sheet Linoleum
MFG: Armstrong Flooring
Style: 38530 Cityscape
Color: NY Minute 38530
Size: 2 m x 25 m x 2 mm



SWF-01
Type: Sprung Wood Flooring
MFG: TBD
Style: Rift Cut White Oak




WF-01
Type: Engineered Wood
Flooring
MFG: Nydree
Style: Rift & Quarter White
Oak



Flooring

EP-01
Type: Epoxy
MFG: Miracote
Style: Marble Chip Flooring
Color: DFS-B-05



CNC-01
Type: Sealed Concrete
Color: Ashford Formula



CNC-02
Type: Polished Concrete
Color: Natural Finish



Interior Finish: SC - Sorensen Center

Walls - Felt Covering


WC-01
MFG: PoshFelt
Style: PSH226
Color: Grove
Size: 3 mm



WC-02
MFG: PoshFelt
Style: PSH227
Color: Succulent
Size: 3 mm



WC-03
MFG: PoshFelt
Style: PSH553
Color: Conifer
Size: 3 mm



WC-04
MFG: FilzFelt
Style: 3 mm Wool Design Felt
Color: 175 Graphit
Size: 70 3/4" W



Walls - Felt Covering

WC-05
MFG: FilzFelt
Style: 3 mm Wool Design Felt
Color: 300 Anthrazit
Size: 70 3/4" W



Walls - Base

WB-01
MFG: Johnsonite
Style: Duracove Rubber
(Type TP)
Color: 27 Mist WG
Size: 4" H



WB-02
MFG: Johnsonite
Style: Duracove Rubber
(Type TP)
Color: 63 Burnt Umber B
Size: 4" H



WB-03
MFG: Johnsonite
Style: Duracove Rubber
(Type TP)
Color: 63 Burnt Umber B
Size: 6" H



Wood Veneer

WV-02
MFG: Wilsonart
Style: Treefrog
Color: Fine Grey Oak Groove



WV-03
MFG: Wilsonart
Style: Treefrog
Color: Walnut Groove




Interior Finish: SC - Sorensen Center

Plastic Laminate


PL-01
MFG: Wilsonart
Style: 7981-12
Color: Landmark Wood



PL-03
MFG: Wilsonart
Style: 15504-31
Color: Charcoal Velvet



PL-04
MFG: Pionite
Style: SV750-SD
Color: Fresh Cut Grass



PL-05
MFG: Wilsonart
Style: 7971K-12
Color: Uptown Walnut




Walls - Panels

FRP-01
MFG: Marlite
Style: S 100G
Color: White



TP-01/UP-01
Type: Toilet/Urinal Partitions
MFG: Bobrick
Style: Duraline Gapless |
1082G.67
Color: Charcoal 0077 FH



VWS-01
Type: Vegetated Wall System
MFG: Garden on the Wall
Style: Garden-Frame
Color: Garden & Foliage,
Preserved Foliage




Furnishings

BB-01
Type: Butcher Block
MFG: Wilsonart
Style: Oiled Countertop
Color: Hevea - Side B




FB-01
Type: Upholstery
MFG: Maharam
Style: 466196 Compound
Color: 017 Vessel



FG-01
Type: Faux Greenery
MFG: Commercial Silk
Style: Hosta HOS212
Size: 12" x 15"




SS-01
Type: Solid Surface
MFG: Hanex Solid Surfaces
Style: B-012
Color: Oslo White



Furnishings


SS-02
MFG: Wilsonart
Style: 9115GS (3)
Color: Zen Grey
Size: 13 mm



ST-01
MFG: Wilsonart
Style: Q1018
Color: Lazio
Size: 3 cm




ST-02
MFG: Wilsonart
Style: Q1009
Color: Grey Lake
Size: 3 cm




Interior Finish: SC - Sorensen Center

Panel Ceiling


APC-01
MFG: USG
Style: Radar
Color: White
Size: 24" x 24"




APC-02
MFG: Armstrong
Style: Clean Room VL
Color: White
Size: 24" x 24"



APC-03
MFG: Armstrong
Style: Mesa Beveled Tegalur
Color: White
Size: 24" x 24"




APC-04
MFG: Armstrong
Style: Optima Tegalur
Color: White
Size: 24" x 24"




Wood Fiber Ceiling

APC-05
MFG: Armstrong
Style: Tectum Shapes
Color: PNT-04
Size: 42" x 66"




APC-06
MFG: Armstrong
Style: Tectum Shapes
Color: PNT-05
Size: 42" x 66"




Wood Ceiling


SC-02
MFG: Geometrik
Style: Geopanel Grille
Color: PNT-02
Size: 1.5" W x 7.5" D



SC-03
MFG: Geometrik
Style: Geopanel Grille
Color: WV-03/04
Size: 1.5" W x 2" D



SC-04
MFG: Geometrik
Style: Geopanel Grille
Color: PNT-04
Size: 1.5" W x 2" D



Interior Finish: SC - Sorensen Center


Lighting

Light Channel

Type: CL1

Mfg: PureEdge Lighting

Model: LCS-3.2W-LENGTH-D40K-SA



Product	Wattage	Nomial Size	Diffuser	Color	Finish
Light Channel .3 Surface Mount	2.5 W	LENGTH 1 @ 25' 1 @ 30' 1 @ 40' Verify Length	Diffuser Lens	4000K Cool White	Satin Aluminum

Downlight

Type: DL1

Mfg: Caliber Plus

Model: 3MAQLD-13-4K-W-W-W-D8-**-**-NF



Fixture Series	Lumens	Color Temp	Beam Dist. Head 1	Beam Dist. Head 2	Beam Dist. Head 2
3MAQLD = 3 Head	13 = 1300L	4K (4000K)	W = 40°	W = 40°	W = 40°

Dimming	Interior Finish	Head Finish	Options
D8 = Xitanium 1%, 0-10V (linear) 120-277VAC	** Verify Finish	** Verify Finish	NF = Flangeless

Downlight

Type: DL2

Mfg: Portfolio

Model: LDSQA4A28840D010TE LAR35FL 4LSQA1H HB26



Housing	Lumens	CRI	CCT	Driver
LDSQA4A = 4" Square Aperture adjustable/slope	28 = 2800 (Non-IC)	8 = 80 CRI	40 = 4000K	D010TE = 120-277V 0-10V 1% dimming or trailing edge 120V

Beam Forming Reflector	Reflector	Finish	Accessories
LAR35FL = 35° optic	4LSQA1 = 4" Adjustable Accent, Self Flanged	H = Semi-Specular Clear	HB26 = C-channel Bar Hanger, 26" Long, Pair

Interior Finish: SC - Sorensen Center

Lighting


Downlight

Type: DL3

Mfg: Portfolio

Model: LDSQ4B20D010 EU4B10208050 4LBSSQ1MW HB26

Housing	Lumens	Voltage	Driver
LDSQ4B = LED Square Downlight 4" Nominal Aperture	20 = 2000 lumens	Blank = 120-277V	D010 = 0-10V Dimming 1% to 100%, 120V-277V



Power Module	Lumen Levels	CRI	Color	Trim	Distribution	Flange	Finish	Accessories
EU4B = 4" Universal LED Module	1020 = 1000, 1500, 2000 lumens	80 = 80 CRI Minimum	50 = 5000K	4LB = 4" LED	PSSQ = Plastic Shallow Non-Conductive	1 = Self-flanged	MW = Matte White	HB26 = C-channel Bar Hanger, 26" Long, Pair


Downlight

Type: DL4

Mfg: Portfolio

Model: DSQ4B20D010 EU4B10208040 4LBSQ1H HB26

Housing	Lumens	Voltage	Driver
LDSQ4B = LED Square Downlight 4" Nominal Aperture	20 = 2000 lumens	Blank = 120-277V	D010 = 0-10V Dimming, 1% to 100%, 120V-277V



Power Module	Lumen Levels	CRI	Color	Trim	Distribution	Flange	Finish	Accessories
EU4B = 4" Universal LED Module	1020 = 1000, 1500, 2000 lumens	80 = 80 CRI Minimum	40 = 4000K	4LB = 4" LED	SQ = Square Anodized Aluminum	1 = Self-flanged	H = Semi-Specular Clear	HB26 = C-channel Bar Hanger, 26" Long, Pair

Downlight

Type: DL5

Mfg: Portfolio

Model: LD2B15D010 EU2B15FL408040 2LBDSQC1** HB26

Housing	Lumens	Voltage	Driver
LD2B = New Construc- tion Downlight 2" 2000 lumen	15 = 1500 lumens	Blank = 120-277V	D010 = 0-10V Dimming, 1% to 100%, 120V-277V



Power Module	Lumen Levels	CRI	Color	Trim	Distribution	Flange	Finish	Accessories
EU2B = 2" Universal LED Module	15FL40 = 1500 lumen 40° Non IC Rated	80 = 80 CRI minimum	40 = 4000K	2LB = 2" LED	DSQC = Square Cast Downlight	1 = Self- flanged	** = Verify Finish	HB26 = C-channel Bar Hanger, 26" Long, Pair

Interior Finish: SC - Sorensen Center

Lighting

Downlight

Type: DL6

Mfg: Portfolio

Model: LDSQA2B15WFL8040D010 2LBASQC1MMS HB26

Housing	Lumens	Distributuion	CRI	Color
LDSQA2B = New Construction Adjustable 2" Nominal Aperture	15 = 1500 lumens	WFL = 55° optic	80 = 80 CRI minimum	40 = 4000K

Voltage	Driver	Trim	Reflector	Flange	Finish	Accessories
Blank = 120-277V	D010 = 0-10V Dimming 1%-100%, 120-277V	2LB = 2" trim	ASQC = Square cast aluminum	1 = Self-flanged	MMS = Matte Metallic Silver	HB26 = Pair C-channel bar hanger, 26" long



Downlight

Type: DL7

Mfg: Portfolio

Model: LD4B20D010 EU4B10209040 4LBSW1H HB26

Housing	Lumens	Voltage	Driver
LD4B = LED Downlight 4" Nominal Aperture	20 = 2000 lumens	Blank = 120-277V	D010 = 0-10V Dimming, 1% to 100%, 120V-277V

Power Module	Lumen Levels	CRI	Color	Trim	Distribution	Flange	Finish
EU4B = 4" Universal LED Module	1020 = 1000, 1500, 2000 lumens	90 = 90 CRI Minimum	40 = 4000K	4LB = 4" LED	SW = Single Wall Wash	1 = Self-flanged	H = Semi-Specular Clear



Pendant

Type: LL1

Mfg: PureEdge Lighting

Model: CSDH-7W-4S-48-40K-**

System	Wattage Per Foot	Canopy	Nominal Size	Color	Finish
CSDH = Cirrus Suspension Diffused Lens High Efficiency	7W = 7.5 Watt (160" max, 13.3')	4S = 4.6" Square Canopy	48 = 48"	40 = 4000K	** = Verify Finish



Pendant

Type: LL1 - Alternate

Mfg: PureEdge Lighting

Model: CSDH-7W-4S-12-40-**

System	Wattage Per Foot	Canopy	Nominal Size	Color	Finish
CSDH = Cirrus Suspension Diffused Lens High Efficiency	7W = 7.5 Watt (160" max, 13.3')	4S = 4.6" Square Canopy	12 = 12"	40 = 4000K	** = Verify Finish



Interior Finish: SC - Sorensen Center

Lighting

Pendant


Type: LL2
Mfg: PureEdge Lighting
Model: CSDH-7W-4S-96-40K-**



System	Wattage Per Foot	Canopy	Nominal Size	Color	Finish
CSDH = Cirrus Suspension Diffused Lens High Efficiency	7W = 7.5 Watt (160" max, 13.3')	4S = 4.6" Square Canopy	96 = 96"	40 = 4000K	** = Verify Finish

Pendant


Type: LL3
Mfg: PureEdge Lighting
Model: CSDH-7W-4S-60-40K-**



System	Wattage Per Foot	Canopy	Nominal Size	Color	Finish
CSDH = Cirrus Suspension Diffused Lens High Efficiency	7W = 7.5 Watt (160" max, 13.3')	4S = 4.6" Square Canopy	60 = 60"	40 = 4000K	** = Verify Finish

Pendant

Type: LL4
Mfg: PureEdge Lighting
Model: CSDH-7W-4S-90-40K-**



System	Wattage Per Foot	Canopy	Nominal Size	Color	Finish
CSDH = Cirrus Suspension Diffused Lens High Efficiency	7W = 7.5 Watt (160" max, 13.3')	4S = 4.6" Square Canopy	90 = 90"	40 = 4000K	** = Verify Finish

Pendant


Type: LL5
Mfg: PureEdge Lighting
Model: CSDH-7W-4S-72-40K-**



System	Wattage Per Foot	Canopy	Nominal Size	Color	Finish
CSDH = Cirrus Suspension Diffused Lens High Efficiency	7W = 7.5 Watt (160" max, 13.3')	4S = 4.6" Square Canopy	72 = 72"	40 = 4000K	** = Verify Finish

Pendant

Type: LL6
Mfg: Nulite Lighting
Model: RP13-D-FF-08-H40-1C-U-D-**-**-**-8'



Series	Direct Shielding	Lumen Package	CRI/CCT	Circuit
RP13-D = Regolo 1.5" wide, 3" tall direct integral pendant	FF = Flush Frosted	08 = 750 lm/ft	H40 = 90 CRI 4000K	1C = Single Circuit

Voltage	Driver	Luminaire	Canopy	Mounting/Suspension	Length
U = Universal	D - Dim to 1% (Standard)	** = Verify Finish	** = Verify Finish	** = Verify Length	** = 8 ft

Interior Finish: SC - Sorensen Center

Lighting

Pendant


Type: LL7

Mfg: Nulite Lighting

Model: RP13-D-FF-08-H40-1C-U-D-**-**-**-4'

Series	Direct Shielding	Lumen Package	CRI/CCT	Circuit
RP13-D = Regolo 1.5" wide, 3" tall direct integral pendant	FF = Flush Frosted	08 = 750 lm/ft	H40 = 90 CRI 4000K	1C = Single Circuit

Voltage	Driver	Luminaire	Canopy	Mounting/Suspension	Length
U = Universal	D - Dim to 1% (Standard)	** = Verify Finish	** = Verify Finish	** = Verify Length	** = 4 ft



Pendant

Type: LL8

Mfg: PureEdge Lighting

Model: CSDH-7W-4S-36-40K-**-**

System	Wattage Per Foot	Canopy	Nominal Size	Color	Finish
CSDH = Cirrus Suspension Diffused Lens High Efficiency	7W = 7.5 Watt (160" max, 13.3')	4S = 4.6" Square Canopy	36 = 36"	40 = 4000K	** = Verify Finish



Pendant

Type: LL9

Mfg: PureEdge Lighting

Model: CSDH-7W-4S-24-40K-**-**

System	Wattage Per Foot	Canopy	Nominal Size	Color	Finish
CSDH = Cirrus Suspension Diffused Lens High Efficiency	7W = 7.5 Watt (160" max, 13.3')	4S = 4.6" Square Canopy	24 = 24"	40 = 4000K	** = Verify Finish



Interior Finish: SC - Sorensen Center


Lighting

Zip Suspension

Type: LL10

Mfg: PureEdge Lighting

Model: ZSDM-7W-LENGTH-40K-SN, CS-ADJ-SWAG-SN,
SDM-CAP-2R-SN, ZSDM-CA-SN, ZSM-SPD-2R-SN,
ZSM-SC-SN, ZSDM-LNC-SN



System	Wattage Per Foot	Nominal Size	Color	Finish
ZSDM = Zip Suspension, Diffused White 100° Standard Efficiency, Modular, without Louver	7W = 7.5 Watt	LENGTH = Verify Length	40 = 4000K	SN = Satin Finish

Product	Type	Finish
CS = Channel Suspension	ADJ-SWAG = Adjustable Swag Hook for Static White	SN = Satin Nickel

System	Type	Power Canopy	Finish
SDM = Zip Suspension Modular Downlight	CAP = End Cap Power	2R = 2.8" Round Canopy	SN = Satin Finish

System	Type	Finish
ZSDM = Zip Suspension Modular Downlight	CA = End Cap Power	SN = Satin Nickel

System	Type	Power Canopy	Finish
ZSM = Zip Suspension Modular Downlight	SPD = Straight Power Connector, Dual Circuit	2R = 2.8" Round Canopy	SN = Satin Finish

System	Type	Finish
ZSM = Zip Suspension Modular Downlight	SC = Conductive Straight Connector	SN = Satin Nickel


System	Type	Finish
ZSDM = Zip Suspension Modular Downlight	LNC = L-Shaped Non-Conductive Connector	SN = Satin Nickel

Zip Suspension

Type: LL11

Mfg: PureEdge Lighting

Model: ZSDM-7W-LENGTH-40K-SN, CS-ADJ-SWAG-SN,
SDM-CAP-2R-SN, ZSDM-CA-SN, ZSM-SPD-2R-SN,
ZSM-SC-SN, ZSDM-LNC-SN, CS-ADJ-SWAG-SN



System	Wattage Per Foot	Nominal Size	Color	Finish
ZSDM = Zip Suspension, Diffused White 100° Standard Efficiency, Modular, without Louver	7W = 7.5 Watt	LENGTH = Verify Length	40 = 4000K	SN = Satin Finish

Product	Type	Finish
CS = Channel Suspension	ADJ-SWAG = Adjustable Swag Hook for Static White	SN = Satin Nickel

System	Type	Power Canopy	Finish
SDM = Zip Suspension Modular Downlight	CAP = End Cap Power	2R = 2.8" Round Canopy	SN = Satin Finish

System	Type	Finish
ZSDM = Zip Suspension Modular Downlight	CA = End Cap Power	SN = Satin Nickel

System	Type	Power Canopy	Finish
ZSM = Zip Suspension Modular Downlight	SPD = Straight Power Connector, Dual Circuit	2R = 2.8" Round Canopy	SN = Satin Finish

System	Type	Finish
ZSM = Zip Suspension Modular Downlight	SC = Conductive Straight Connector	SN = Satin Nickel

System	Type	Finish
ZSDM = Zip Suspension Modular Downlight	LNC = L-Shaped Non-Conductive Connector	SN = Satin Nickel

Product	Type	Finish
CS = Channel Suspension	ADJ-SWAG = Adjustable Swag Hook for Static White	SN = Satin Nickel

Interior Finish: SC - Sorensen Center


Lighting

Pendant

Type: LL12
Mfg: Prudential LTG
Model: BIO2-LIN-LED4-90-SO-8'-TMWMWW-D1W-SC-UNV-
CA48-**-DM01

Series	LED Color	Output	Nominal Length	Color
BIO2-LIN = Linear	LED4-90 = 90 CRI	SO = Standard	8' = 8 ft	TMW = Textured Matte White

Shielding	Distribution	Circuiting	Voltage	Mounting	Ceiling System	Drivers
MWW = Acrylic Wall Wash Lens	D1W = Wall Wash	SC = Single Circuit	UNV = 120-277V	CA48 = 96 or 144" Aircraft Cable	** = Verify Ceiling System	DM01 = 0-10v 1% Dimming




Pendant

Type: LL13
Mfg: Nulite Lighting
Model: RP13-D-FF-08-H40-1C-U-D-**-**-**
2' x 3' x 3' x 2' x 3' x 3' HEXAGON

Series	Direct Shielding	Lumen Package	CRI/CCT	Circuit
RP13-D = Regolo 1.5" wide, 3" tall direct integral pendant	FF = Flush Frosted	08 = 750 lm/ft	H40 = 90 CRI 4000K	1C = Single Circuit

Voltage	Driver	Luminaire	Canopy	Mounting/Suspension	Shape
U = Universal	D - Dim to 1% (Standard)	** = Verify Finish	** = Verify Finish	** = Verify Length	Hexagon




Recessed

Type: NL1
Mfg: Prudential LTG
Model: P23-PER-REG3-LED4-SO-R22'-TMW MWG-D1G-WTW-SC-
UNV-**-DM01

Series	Lens Position	LED Color	Output	Nominal Length
P23-PER = Perimeter	REG3 = 3 Regressed Lens (NA with Wall Wash)	LED4 = 4000K	SO = Standard	R22' = (Row Length)

Trim Color	Shielding	Distribution	Mounting	Circuiting	Voltage	Ceiling System	Drivers
TMW = Textured Matte White	MWG = Acrylic Wall Grazer lens (D1G Only)	D1G = Wall Grazer (MWG Only)	MTW = Wall to Wall	SC = Single Circuit	UNV = (120-277)	** = Verify Ceiling	DM01 = 0-10v, 1% Dimming



Interior Finish: SC - Sorensen Center

Lighting

Recessed


Type: NL1 - Alternative

Mfg: Prudential LTG

Model: P23-PER-REG3-LED4-SO-24'-TMWMWG-D1G-WTW-SC-UNV-X7-DM10

Series	Lens Position	LED Color	Output	Nominal Length
P23-PER = Perimeter	REG3 = 3 Regressed Lens (NA with Wall Wash)	LED4 = 4000K	SO = Standard	R24' = (Row Length)

Trim Color	Shielding	Distribution	Mounting	Circuiting	Voltage	Ceiling System	Drivers
TMW = Textured Matte White	MWG = Acrylic Wall Grazer lens (D1G Only)	D1G = Wall Grazer (MWG Only)	MTW = Wall to Wall	SC = Single Circuit	UNV = (120-277)	X7 = Hard Ceiling Trimless Mud-over Concealed Flange	DM10 = 0-10v, 10% Dimming



Pendant

Type: NL2-8

Mfg: Prudential LTG

Model: BPRO2-REC-FLSH-LED4-90-SO-8'-TMW-SAL-SC-UNV-**-DM01

Series	Lens Position	LED Color	Output	Nominal Length	Trim Color
BPRO2-REC = BionicPro2	FLSH = Flush Lens	LED4-90 = 90 CRI	SO = Standard	8'	TMW = Textured Matte White

Distribution	Circuiting	Voltage	Ceiling System	Drivers
SAL = Satin Lense	SC = Single Circuit	UNV = (120-277)	** = Verify Finish	DM01 = 0-10v, 1% Dimming



Pendant

Type: NL2-16

Mfg: Prudential LTG

Model: BPRO2-REC-FLSH-LED4-90-SO-16'-TMW-SAL-SC-UNV-**-DM01

Series	Lens Position	LED Color	Output	Nominal Length	Trim Color
BPRO2-REC = BionicPro2	FLSH = Flush Lens	LED4-90 = 90 CRI	SO = Standard	16'	TMW = Textured Matte White

Distribution	Circuiting	Voltage	Ceiling System	Drivers
SAL = Satin Lense	SC = Single Circuit	UNV = (120-277)	** = Verify Finish	DM01 = 0-10v, 1% Dimming



Interior Finish: SC - Sorensen Center

Lighting

Recessed

Type: NL3-6

Mfg: Prudential LTG

Model: P43-PSTD-FLSH-LED4-HO-6'-TMWSAL-D1-**-SC-**-UNV-
DM10 2' x 3' x 3' x 2' x 3' x 3' HEXAGON

Series	Lens Position	LED Color	Output	Nominal Length
P43-PSTD = Standard	FLSH = Flush Lens	LED4 = 4000K	HO = High	6'

Trim Color	Shielding	Distribution	Mounting	Circuiting	Ceiling System	Voltage	Drivers
TMW = Textured Matte White	SAL = Satin Lense	D1 = Direct	** = Verify	SC = Single Circuit	** = Verify	UNV = (120-277)	DM10 = 0-10v, 10% Dimming



Recessed

Type: NL3-10

Mfg: Prudential LTG

Model: P43-PSTD-FLSH-LED4-HO-10'-TMWSAL-D1-**-SC-**-UNV-
DM10 2' x 3' x 3' x 2' x 3' x 3' HEXAGON

Series	Lens Position	LED Color	Output	Nominal Length
P43-PSTD = Standard	FLSH = Flush Lens	LED4 = 4000K	HO = High	10'

Trim Color	Shielding	Distribution	Mounting	Circuiting	Ceiling System	Voltage	Drivers
TMW = Textured Matte White	SAL = Satin Lense	D1 = Direct	** = Verify	SC = Single Circuit	** = Verify	UNV = (120-277)	DM10 = 0-10v, 10% Dimming



Recessed

Type: NL4

Mfg: PMC Lighting

Model: S9062-D-FL/TRM-40K-070-8'-**-UNVOE

Series	Distribution	Mounting	Color Temp	Lumen Output
S9062	D = Direct	FL/TRM = Trimles for mud in application	40K = 4000K	070 = 700 LM/FT - 3.8W/FT

Length	Finish	Voltage	Options
8' = 8 ft or 96"	** = Verify	UNV = (120-277)	OE = Open End



Interior Finish: SC - Sorensen Center

Lighting

Recessed

Type: NL5

Mfg: Prudential LTG

Model: BPRO2-REC-FLSH-LED4-90-SO-4'-TMW-SAL-SC-UNV-**-DM01

Series	Lens Position	LED Color	Output	Nominal Length	Trim Color
BPRO2-REC = BionicPro2	FLSH = Flush Lens	LED4-90 = 90 CRI	SO = Standard	4'	TMW = Textured Matte White
Distribution	Circuiting	Voltage	Ceiling System	Drivers	
SAL = Satin Lense	SC = Single Circuit	UNV = (120-277)	** = Verify Finish	DM01 = 0-10v, 1% Dimming	



Recessed

Type: NL6

Mfg: Prudential LTG

Model: BPRO2-REC-FLSH-LED4-90-SO-6'-TMW-SAL-SC-UNV-**-DM01

Series	Lens Position	LED Color	Output	Nominal Length	Trim Color
BPRO2-REC = BionicPro2	FLSH = Flush Lens	LED4-90 = 90 CRI	SO = Standard	6'	TMW = Textured Matte White
Distribution	Circuiting	Voltage	Ceiling System	Drivers	
SAL = Satin Lense	SC = Single Circuit	UNV = (120-277)	** = Verify Finish	DM01 = 0-10v, 1% Dimming	



Recessed

Type: NL7

Mfg: Prudential LTG

Model: BPRO2-REC-FLSH-LED4-90-SO-4'-TMW-SAL-SC-UNV-**-DM01

Series	Lens Position	LED Color	Output	Nominal Length	Trim Color
BPRO2-REC = BionicPro2	FLSH = Flush Lens	LED4-90 = 90 CRI	SO = Standard	4'	TMW = Textured Matte White
Distribution	Circuiting	Voltage	Ceiling System	Drivers	
SAL = Satin Lense	SC = Single Circuit	UNV = (120-277)	** = Verify Finish	DM01 = 0-10v, 1% Dimming	



Recessed

Type: NL9

Mfg: Prudential LTG

Model: BPRO2-REC-FLSH-LED4-90-MOLENGTH-TMW-SAL-SC-UNV-**-DM01

Series	Lens Position	LED Color	Output	Nominal Length	Trim Color
BPRO2-REC = BionicPro2	FLSH = Flush Lens	LED4-90 = 90 CRI	MO = Medium	LENGTH = Verify	TMW = Textured Matte White
Distribution	Circuiting	Voltage	Ceiling System	Drivers	
SAL = Satin Lense	SC = Single Circuit	UNV = (120-277)	** = Verify Finish	DM01 = 0-10v, 1% Dimming	



Interior Finish: SC - Sorensen Center

Lighting

Pendant

Type: PL1
Mfg: Acord Lighting
Model: 1343- ** 42081 (ACC, GRNLT)
Description: Conical Accord Pendant 1343 - Verify Finish



Pendant

Type: PL2
Mfg: Acord Lighting
Model: (1) 1224 MULTIFACETED ** (2) 42081(ACC, GRNLT)
Description: Diamond Accord Pendant 1224 - Verify Finish



Pendant

Type: PL3
Mfg: Artemide
Model: SP09590A 4000K GREEN RAL 6002 OUTER FINISH
Description: Diamond Accord Pendant 1224 - Verify Finish

Series	CCT	Color	Control	Lumens
SP09590A	4000K	Green RAL 6002	Dimmable 0-10V	1816 lm



Pendant

Type: PL3A
Mfg: Artemide
Model: SP09590B 4000K SILVER RAL 9007 OUTER FINISH
Description: Diamond Accord Pendant 1224 - Verify Finish

Series	CCT	Color	Control	Lumens
SP09590A	4000K	Silver RAL 9007	Dimmable 0-10V	1816 lm



Pendant

Type: PL3B
Mfg: Artemide
Model: SP09590C 4000K BLACK OUTER FINISH
Description: Diamond Accord Pendant 1224 - Verify Finish

Series	CCT	Color	Control	Lumens
SP09590A	4000K	Black	Dimmable 0-10V	1816 lm



Pendant

Type: PL5
Mfg: Artemide
Model: SP09590C 4000K BLACK OUTER FINISH
Description: Diamond Accord Pendant 1224 - Verify Finish

Series	CCT	Color	Control	Lumens
SP09590A	4000K	Black	Dimmable 0-10V	3665.15 lm



Interior Finish: SC - Sorensen Center

Lighting

Pendant

Type: PL5A
Mfg: Artemide
Model: SP09590E 4000K SILVER RAL 9007 OUTER FINISH
Description: Diamond Accord Pendant 1224 - Verify Finish

Series	CCT	Color	Control	Lumens
SP09590A	4000K	Green RAL 6002	Dimmable 0-10V	3665.15 lm



Pendant

Type: PL5B
Mfg: Artemide
Model: SP09590F 4000K BLACK OUTER FINISH
Description: Diamond Accord Pendant 1224 - Verify Finish

Series	CCT	Color	Control	Lumens
SP09590A	4000K	Black	Dimmable 0-10V	3665.15 lm



Pendant

Type: PL6
Mfg: Fabbian
Model: D81A03A48
Description: Pendant lamp with aluminium cover and dark wood

Series	CCT	Color	Control	Lumens
SP09590A	4000K	Silver RAL 9007	Dimmable 0-10V	1816 lm



Pendant

Type: PL7
Mfg: Cooper Lighting Solutions
Model: HCC4S20D010** HM412840 41MDC HCAC120**

Cylinder	Lumens	Control	Finish	LED Module
HCC4S = 4" surface mount cylinder	20 = 2000 lumens	D010 = 120-277VAC 50/60Hz, 0-10V analog 1%-100% dimming	** = Verify	HM4 = 4" module

Lumens	CRI / CCT	Reflector	Distribution	Finish	Flange
12 = 1000, 1500, 2000 lumens	840 = 80 CRI, 4000K CCT	41 = 4" self-flanged, conical reflector	MD = medium reflector 61° beam angle, 1.00 SC	C = Specular clear	Blank = Polished flange standard with C & H reflectors




Interior Finish: SC - Sorensen Center

Lighting

Recessed


Type: RL1
Mfg: Cooper Lighting Solutions
Model: 24FPSL2SCT3



SKU	UPC	Lumens			Power	Efficacy			Input Current (A)	
24FPSL2SCT3	080083889365	3430	3534	3628	30.2	113.6	117	120.1	.25	.11
		4504	4642	4795	41.5	108.5	111.9	115.5	.35	.15
		6033	6249	6441	60.5	99.7	103.3	106.5	.5	.22

Recessed


Type: RL2
Mfg: Cooper Lighting Solutions
Model: 22FPSL2SCT3



SKU	UPC	Lumens			Power	Efficacy			Input Current (A)	
22FPSL2SCT3	080083889402	1810	1864	1909	16	113.1	116.5	119.3	.13	.06
		2612	2694	2736	24.1	108.4	111.8	113.5	.2	.09
		3165	3268	3349	30.4	104.1	107.5	110.1	.25	.11

Recessed

Type: RL3
Mfg: Cooper Lighting Solutions
Model: 22FPSL2SCT3 DF-22W-U



SKU	UPC	Lumens			Power	Efficacy			Input Current (A)	
22FPSL2SCT3	080083889402	1810	1864	1909	16	113.1	116.5	119.3	.13	.06
		2612	2694	2736	24.1	108.4	111.8	113.5	.2	.09
		3165	3268	3349	30.4	104.1	107.5	110.1	.25	.11

Recessed

Type: SL1
Mfg: McGraw-Edison
Model: TT-C5-LED-E1-WQ-**-**-7050-UPL



Product Family	Lumen Package	Lamp Type	Voltage	Distribution
TT = TopTier	C5 = Nominal 9,500 Lumens	LED = Solid State Light Emitting Diodes	E1 = Electrical (120-277V)	WQ = Wide


Mounting	Options	Options
[BLANK] = Surface or Pendant Mount	7050 = 70 CRI / 5000K	UPL = Uplight

Interior Finish: SC - Sorensen Center

Lighting

Recessed

Type: SL2
Mfg: Cooper Lighting Solutions
Model: 24FPSL2SCT3 FPXSURF24



SKU	UPC	Lumens			Power	Efficacy			Input Current (A)	
24FPSL2SCT3	080083889365	3430	3534	3628	30.2	113.6	117	120.1	.25	.11
		4504	4642	4795	41.5	108.5	111.9	115.5	.35	.15
		6033	6249	6441	60.5	99.7	103.3	106.5	.5	.22

Surface Mount Kit

Catalog	UPC	Size
FPXSURF24	080083867400	2x4

Pendant

Type: TR1
Mfg: Times Square Lighting
Model: AXT13-83-40-**-120-ZO-T1-TE



Module	LED Module	Color Temp	Finish	Voltage
AXT13	83	40 = 4000K	** = Verify	120

Optics	Mounting Options	Dimming
ZO = 15° - 60°	T1 = Track Adapter for commercial grade 1 & 2 circuit track. 120V. For use with larger, heavier fixtures	TE = Trailing Edge

Wall Strip

Type: VL1
Mfg: PureEdge Lighting
Model: TXW2-5W-1RE-22.4"-40K-*/PSB-2X96W-UNI-24VDC



System	Wattage	Canopy	Nominal Size	Color Temp
TXW2 = Tie Stix Wall 2-Light	5W = 5 Watts	1RE = 1" Rectangle with Junction Box	22.4 = 22.4"	40K = 4000K Cool White

Hardware Finish	Channel Finish	Dimmer
* = Verify	** = Verify	PSB-2X96W-UNI-24VDC

Interior Finish: SC - Sorensen Center

Lighting

Wall Lamp

Type: WL1
Mfg: Rebelle
Model: 6004-134L-5K-277-T3-DIM-**

Model	Watts	Color Temp	Volt	Distribution
6004	134L = 1 x 134 watts 12400 lumens	5K = 5000K	277	T3 = Type III Distribution

Options	Exterior Color
DIM = 0 - 10 volt dimmable driver	** = Verify



Wall Lamp

Type: WL3
Mfg: Rebelle
Model: 6003-1200LMN-5K-277-T4-DIM-**

Model	Watts	Color Temp	Volt	Distribution
6003	1200LMN = 1,200 lumens	5K = 5000K	277	T4 = Type IV Distribution

Options	Exterior Color
DIM = 0 - 10 volt dimmable driver	** = Verify



Wall Lamp

Type: WL4
Mfg: Rebelle
Model: 6004-4500LMN-5K-277-T4-DIM-**

Model	Watts	Color Temp	Volt	Distribution
6004	4500LMN = 4,500 lumens	5K = 5000K	277	T4 = Type IV Distribution

Options	Exterior Color
DIM = 0 - 10 volt dimmable driver	** = Verify



Wall Lamp

Type: WL5
Mfg: Rebelle
Model: 6004-10000LMN-5K-277-T4-DIM-**

Model	Watts	Color Temp	Volt	Distribution
6004	10000LMN = 10,000 lumens	5K = 5000K	277	T4 = Type IV Distribution

Options	Exterior Color
DIM = 0 - 10 volt dimmable driver	** = Verify



Interior Finish: SC - Sorensen Center


Lighting

Pendant

Type: WL6
Mfg: Prudential LTG
Model: BIO2-LIN-LED490-SO-LENGTH-**-MWG-D1G-SC-
UNV-WS-DM10

Series	LED Color	Output	Nominal Length	Color
BIO2-LIN = Linear	LED4-90 = 90 CRI	SO = Standard	LENGTH	** = Verify

Shielding	Distribution	Circuiting	Voltage	Mounting	Drivers
MWW = Acrylic Wall Wash Lens	D1G = Wall Grazer	SC = Single Circuit	UNV = 120-277V	WS = Wall Spacer	DM10 = 0-10v 1% Dimming



Wall Lamp

Type: WL7
Mfg: Rebelle
Model: 6005-200L-5K-277-T4-DIM-**-**

Model	Watts	Color Temp	Volt	Distribution
6005	200L = 1 x 200 watts 18,600 lumens	5K = 5000K	277	T4 = Type IV Distribution

Options	Exterior Color
DIM = 0 - 10 volt dimmable driver	** = Verify



Wall Lamp

Type: WL8
Mfg: Rebelle
Model: 6005-134L-5K-277-T4-DIM-**-**

Model	Watts	Color Temp	Volt	Distribution
6005	134L = 1 x 134 watts 12400 lumens	5K = 5000K	277	T4 = Type IV Distribution

Options	Exterior Color
DIM = 0 - 10 volt dimmable driver	** = Verify



Interior Finish: SC - Sorensen Center

Lighting

Display

Type: YL1
Mfg: Cooper Lighting
Model: 4SNLED-LD5-56SL-LW-UNV-L840-CD1-U AYC-CHAIN/
SET



Length	Series	Lamp Type	LED Packages	Lens
4 = 4 ft.	SNLED = Commercial LED Striplight	LD5 = LED 5.0	56SL = 4 ft. Round Lens	LW = Full Frost Lens - Wide

Voltage	Color Temp	Drivers	# of Drivers	Packaging	Accessories
UNV = Universal Voltage 120-277	L840 = 4000K 80 CRI	CD = 0-10V Dimming (10%-100%)	1 = 1 Driver	U = Unit Pack	AYC-Chain/Set = 36" Chain Hanger (Use 1 set per fixture)

Display

Type: YL2
Mfg: Cooper Lighting
Model: 8TSNLED-LD5-110HL-LW-UNV-L840-CD1-U AYC-
CHAIN/SET



Length	Series	Lamp Type	LED Packages	Lens
8T = 8 ft.	SNLED = Commercial LED Striplight	LD5 = LED 5.0	110HL = 8 ft. Round Lens	LW = Full Frost Lens - Wide


Voltage	Color Temp	Drivers	# of Drivers	Packaging	Accessories
UNV = Universal Voltage 120-277	L840 = 4000K 80 CRI	CD = 0-10V Dimming (10%-100%)	1 = 1 Driver	U = Unit Pack	AYC-Chain/Set = 36" Chain Hanger (Use 1 set per fixture)

Interior Finish: SC - Sorensen Center

Doors


HMD1

Type: Hollow Metal
Style: Glass Door 5/8"
Tempered Monolithic
Color: Black Anodized Shoe




HMD2

Type: Insulated Hollow Metal
Style: Aluminum Pivot Door
Color: Black Anodized Shoe



HMD3


Type: Double Hollow Metal
Style: Single Solid Core Wood



Doors


HMD4

Type: Insulated Double Hollow Metal
Style: Single Solid Core Wood
with Vision Panel




HMD5

Type: Hollow Metal
Style: Tempered Vision Panel



WD1


Type: Solid Core Wood
Style: Glass Pivot Door
Color: Black Anodized Aluminum



Doors


WD2

Type: Solid Core Wood
Style: Tempered Vision Panel
Color: Black Anodized Aluminum




WD3

Type: Doubled Solid Core Wood
Style: Wood Slider Door



WD4

Type: Solid Core Wood
Style: Full Lite




Interior Finish: SC - Sorensen Center

Doors


WD5

Type: Double Solid Core Wood
Style: Tempered Vision Panel
Color: Black Anodized Shoe




WD6

Type: Solid Core Door
Style: Aluminum Pivot Door
Color: Black Anodized Shoe



GL1


Type: Tempered Glass
Style: Single Solid Core Wood



Doors


GL2

Type: Double Tempered Glass
Style: Single Solid Core Wood with Vision Panel




GL3

Type: Frameless Tempered Glass
Style: Double Solid Core Wood



GL4


Type: Double Frameless Tempered Glass
Style: Glass Pivot Door
Color: Black Anodized Aluminum



Doors


IIA1

Type: Tempered Glass Slider
Style: Glass Slider Door
Color: Black Anodized Aluminum




IIA2

Type: Framless Tempered Glass Slider
Style: Wood Slider Door



SP1

Type: Tempered Glass
Style: Wood Slider Door with Vision Panel



Interior Finish: SC - Sorensen Center

Door Hardware

Pull Bar

Mfg: Ives
Description: Offset long door pull, rounded tip
Finish: Black

Product Number	Projection	Clearnace	Offset	Length	CTC
9264-36-20	2-3/4"	1-1/2"	3-5/8"	36"	20"



Push Bar

Mfg: Schlage Electronics
Description: Latchbolt retracted by lever
Finish: US26D, SPBLK, 315



Latch Lever

Mfg: Schlage
Description: Latchbolt retracted by lever
Finish: 626, 622



L9496
Privacy
Latch



L9010
Passage
Latch



L9080EL/EU
RX Electrified
Lock



L/LV9050
Office/Inner
Entry Lock



L/LV9070
Classroom
Lock



L/LV9080
Storeroom
Lock

