# Skill 19-2 Evaluation Checklist

**Objective 11:** Raise and lower a telescoping aerial device equipped with a platform. [NFPA® 1002, 6.2.3]

Student Name:	Date:	

#### **Directions**

For this skills evaluation checklist, students will raise and lower a telescoping aerial device equipped with a platform. This skill requires two firefighters: one to operate the apparatus and one to assist as a spotter. Always follow manufacturer's recommendations and local standard operating procedures (SOPs) when performing all procedures.

#### Resources

- Appropriate PPE
- Telescoping aerial device equipped with a platform
- Manufacturer's operator's manual
- Instructor-approved objective (target)

### **Criteria & Evaluation Comments**

Criteria (determined by	the AHJ)		
After the candidate has	completed the	e skill sheet, write comments b	elow.
Evaluator/Candidate Cor	nments		
		*	
Pass	Fail		
1 433	i dii		
EI C:			
Evaluator Signature	Date	Student Signature	Date

## **Skills Evaluation Checklist**

**Objective 11:** Raise and lower a telescoping aerial device equipped with a platform. [NFPA® 1002, 6.2.3]

	Task Steps	Yes	No
	Raising the Telescoping Platform Device		
1.	Stabilize the apparatus.  WARNING: Failure to properly stabilize the apparatus could result in tipping the apparatus.		
2.	Unlock the aerial device from its cradle if so equipped.		
3.	Check the intended path of the aerial device for obstructions.		
	<b>Note:</b> If raising an aerial platform, steps 4 through 20 should be performed by the student first at the primary control position (lower) and then in the secondary control position(s) (platform, pump panel) so that the candidate raises and lowers the aerial device from each position.		
4.	Energize the platform controls from the primary position to enable the platform controls.		
5.	Elevate the device out of the cradle.		
6.	Check the load chart to determine load capacity.		
7.	Allow personnel to board the aerial platform.  WARNING: Fall Hazard! When the device is in motion, use fall protection on ladders and in the platform. Failure to comply may injure or kill.		
8.	Elevate the aerial device.		
9.	Rotate the aerial device.		
10.	Extend the aerial device.  a. Align the rungs in preparation for personnel to climb the ladder (if so equipped).  WARNING: Pinch or Crush Hazard! Never extend or retract with people on ladder. Failure to comply may injure or kill.		
11.	Lower the aerial device to the objective, positioning device above the surface of the objective to a height indicated by the department's SOPs.		

	Stowing the Telescoping Platform Device	
12.	Remove all personnel from the aerial ladder (if so equipped) before attempting any part of the lowering process.	
13.	Ensure the waterway system is drained.	
14.	Elevate the platform away from its objective.	
15.	If required, lower the platform and allow personnel to exit platform.	
	<b>Note:</b> Lower the platform sufficiently to allow personnel to exit the platform without the platform actually making contact with the ground.	
16.	Elevate and retract the aerial device.	
17.	Rotate the aerial device until it is positioned directly above its travel cradle.	
18.	Lower the aerial device to the cradle.	
19.	Ensure that the device is firmly seated and that the hold-down locks have engaged if so equipped or power the aerial into the cradle per manufacturer's recommendations.	
20.	Activate the hold-down locks if they did not automatically activate when the device was bedded if so equipped.	